

Hydrokleen Wastewater Filtration

HES1 - 3 Compartment Above Ground Oil Water Separator

Hydrokleen HE/S1 is an affordable, efficient, easy to maintain, low energy above ground oil water separator that is primarily focused on removing two major waste contributors in wash wastewater: oil and suspended solids. Wastewater treatment using HE/S1 technology is often all that is required to meet wastewater discharge requirements.

Standard Features

- Gravity Flow Through Design
- 120 volt, 1 phase, 60 Hz
- Self-cleaning Tanks
- Overflow Protection Device
- Overflow gravity discharge
- Automatic oil skimming and decanting

Optional Features

- Pressurized Discharge To Drain
- Automatic Tank Sludge Drains
- Sump Pump Discharge
- Circulation/Aeration System
 - For Enhanced Oil Coalescing
- Biological Odor Control And Hydrocarbon Elimination
 - With Hydro Biodigester Dosing



Specifications

Flow Rate - GPM (LPM)	12 (45.4)
Dimensions, Inches (cm)	61 (155) L X 34 (86.4) W X 59 (150) H
Weight, Lbs (kg)	520 (235.8)

Standard	
Volts (60Hz)	120V-1P
Amps (60Hz)	0.5

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)