



865 West 2600 South, Salt Lake City, UT 84119  
 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

**HYDROBLASTERS - HYDROKLEEN - HYDROPAD**

[www.hydroblaster.com](http://www.hydroblaster.com)

## Model OCS Hydrokleen™

The Hydrokleen Oil Coalescing System (OCS) is an above ground Oil/Water separator. The OCS is an excellent alternative to in ground Oil/Water Separators and with over 68,000 square inches of coalescing plates, you're insured of excellent results!

### Standard Features:

- Gravity flow through design
- Self-cleaning tank makes sludge removal easy
- Automatic belt skimmer
- Oil/Water decanter
- Overflow protection device



Options and Accessories	
<b>Tank &amp; Frame Options</b>	
*1WH557	210GL Tank
1WH558	500GL Tank
2RM066	1050GL Tank
<b>Inlet Fittings/Plumbing Connections</b>	
*KO261	Single Inlet Feed, 1.5" FPT
2KO260	Single Inlet Feed, 3/4" FPT
2KO262	Dual Inlet Feed, 1.5" FPT
2KO264	Inlet Feed, 3" Pipe W/Grommet
2KO263	Inlet Feed, 3" FPT
<b>Discharge Options</b>	
*2KO265	Gravity Discharge, 1.5" FPT
2KO266	Gravity Discharge, 3" FPT
2KO267	Gravity Discharge, 3" PVC Pipe Grommet
<b>Drain Line Control Valves</b>	
*1WV697	Sludge Drain, Manual Valve, 1.5"
1ZJ359	Sludge Drain, W/MBV, Requires Connection To PLC
<b>Drain Line Connections</b>	
*2KF174	Sludge Drain, W/Single 1.5" FPT
2KF175	Sludge Drain, W/Dual 1.5" FPT
<b>Oil Skimming And Handling Options</b>	
*2AL638	Active Belt Oil Skimmer, 115 Volt, 60 Hz
2KC143	Active Belt Oil Skimmer, 220 Volt, 50 Hz
<b>Biological Odor Control</b>	
2AR691	Auto Doser For Biodigester W/AC Adapter

NOTE: \* reflects the standard

### Specifications

Dimension: 210 tank option, 34" x 44" x 86.5"H Weight 550 lbs.  
 500 tank option, 51" x 52" W x 86.5"H Weight 696 lbs.

### How the Hydrokleen™ (OCS) Oil Coalescing System Works:

Our state of the art oil coalescing and skimming systems can be fed by pump or gravity. Emulsified oil and grease are directed through the coalescing media where they accumulate on the surface of the oil attractant material of the plates. Once large enough to float free to the surface the oils are permanently removed from the system by an electric belt skimmer. The automatic skimmer deposits the oils into a decanter where trace amounts of water are directed back into the coalescing tank and oils are dispensed into an oil drum or bucket supplied by the customer.



Quality Assured Firm  
 ISO 9001 Certified



Certified Systems Available