

Hydropad, low profile, gutter is separate Model 4PW163, 7.5'L X 20'W, rated 75 ton per axle

Hydropad above ground steel wash rack systems solve SWPPP requirements for vehicle and equipment wash/collection. Design a wash rack for; drive through or drive-in-back-out, overspray containment walls, awnings, remote control stations, various wash water collection and recycling options, vehicle/wheel and undercarriage wash and raised catwalks.

- Modular design to provide any size wash rack required
- Capture wash water and solid wastes
- Promote EPA and SWPPP compliance
- Easy to deploy or re-deploy

Standard

- 75 ton per axle

Options

- Pad connection kit
- Side wall; 4', 6' and 8'
- Gutter side wall; 4', 6' and 8'
- Rail wall, 4', 6' and 8'



Hydropad wash rack; 40' wide X 45' long, drive thru design, Hydrosite equipment enclosure for wash and recycle equipment. Wash monitors, water cannons and Hydroblaster pressure washer with water and solids flowing to in-ground solids settling with drag conveyors for automatic solids removal. Example only.....design

Specifications

Weight Lbs (kg) - 5578 (2530)

Dimensions Ft (m) 7.5' (2.29)L X 20' (6.1)W X 10" (.25)H

Specifications 2023

Subject to change without notice



Intertek



Certified Systems Available