



Wash - Collect - Recycle

Hydro Engineering, Inc.
865 West 2600 South
Salt Lake City, Utah 84119
hydroblaster.com

Hydroblaster™ - Hydropad™ - Hydrokleen™

Hydroblaster™

MODEL 65E-CHT (Jetting System for CHT Systems)

NSN 4940-015146978
(Electric Motor or Diesel Engine driven)

PART	65E-CHT	65D-CHT
VOLUME (GPM)	6	6
PRESSURE (PSI)	5000	5000
MOTOR / ENGINE (HP)	20 electric	28 diesel
WEIGHT (LBS)	625	735

Meets UL1776 Standard for Outdoor and Wash Bay Applications

Standard equipment:

- Four-wheel steerable trailer with a tow bar and front wheel brakes
- 300' (in 50' lengths) of high pressure hose (rated at 6250 psi)
- Belt-driven triplex plunger pump. 6 gallons per minute at 5,000 psi
- Full instrumentation- pressure gauge, hour meter, and power off/on switch
- 20 HP electric motor, 460 volt, 3-phase, 60 hertz or 28 hp diesel engine.
- Foot valve for system "no hands" operation during jetting
- Lockable enclosure over pump and motor keeps personnel away from moving parts
- Combination tie downs and lifting rings for easy transport on, off and around the ship
- Hose reel stores 300 ft. of jetting hose for simple access during use in tight quarters
- 16" foam-filled pneumatic tires allows the CHT to move through passageways easily



1. Specifications are effective 2016. 2. Specifications are subject to change without notice



Certified Systems Available

Intertek