

# Hydrokleen Wastewater Filtration

## CMAFU2 - Automatic Gravity Filtration

Hydrokleen Model CMAFU-2 is designed for a flow processing filtration rate up to 10 GPM as a stand-alone system or combined with other Hydrokleen components for higher rate performance. Wastewater transferred to a CMAFU-2 is gravity fed through disposable paper filter media for low energy solid/liquid separation. Continued solids collection causes basin fluid level rise that activates automatic media index producing a fresh media surface for continued solids removal and transfers spent media to a collection drying tray.

Hydrokleen CMAFU-2 is offered with choice of media porosity but unique design features of this system promote solids compaction thereby increasing bulk density with time forming a solids deposition bed for capture of even submicron particles. Perfect compliment for any application that will benefit from highly efficient solids recovery.

Contact a Hydro Engineering, Inc. project manager for complete system design and application assistance. Hydrokleen filtration / recycling systems are UL\_979 and CSA certified, and conform to CE standards.

## Standard Features

- Stainless Steel Frame
- Automatic Filter Media Advance
- Spent Media Gravity Discharge
- CMAFU-2 Stand

## Optional Features

- Casters
- Conveyor Cover with Window
- Dual Inlet Feed
- Automatic Pumped Discharge
- Media Catch Container, Steel w/Bag



## Specifications

Flow Rate - GPM (LPM)	10 (37.9)
Filtration Accuracy	Optional Micron Levels
Dimensions, Inches (cm)	64 (162.6) L X 26.5 (67.3) W X 29.5 (74.9) H
Weight, Lbs (kg)	182 (82.6)

	Standard
Volts (60Hz)	120V-1P
Amps (60Hz)	5

## Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)