Hydrokleen Wastewater Filtration

RST - Recycled Water Storage Tank

The RST can be an essential option to a Hydrokleen water filtration and recycling system when an available sewer discharge is not available. Hydrokleen water filtration and recycling systems have a function for automatic discharge to drain. This auto discharge occurs when the system has overfilled with water. If there is no available source for discharge of water, the RST becomes that discharge location. The collected water in the RST then becomes the first source for make up water back to the Hydrokleen system. Contact a Hydro Engineering, Inc. project manager for complete system design and application assistance. Hydrokleen filtration / recycling systems are UL-979 and CSA certified, and conform to CE standards.

Standard Features

210 Gallon Tank
Self-cleaning Tank
Overflow Protection with Manual Drain Valve

Optional Features

500 Gallon Tank
Rotating Beacon for Overfill Warning
Auto Drain Valve
Auto Pump-out to Auxillary System

Specifications

Dimensions, Inches (cm)	34.5 (87.6) L X 34.5 (87.6) W X 96 (243.8) H
Weight, Lbs (kg)	550 (249.5)

Pricing

For complete pricing details,
Submit a quote online below.

Get a Quote

Hydro Engineering Innovation | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

Subject to change without notice

Copyright Hydro Engineering Innovation 2025