

Decontamination System

Hydroblaster 5/3000GHO-WDS

UL1776, CSA and CE certifications

GENERAL SPECIFICATIONS AND USE

Hydroblaster 5/3000GHO-WDS is the most advanced and effective invasive species and watercraft decontamination system available. Features provide simplicity, efficiency, convenience, maximum safety, with ultimate performance for unparalleled real world applications. In combination, Hydromat wastewater collection assures simple and portable environmental compliance.

Standard:

- · Gasoline Engine
- 2400 Watt Generator
- Battery
- Full Locking Equipment Enclosure Schedule 80 Coil Warranty
- Control Panel
- 6 Gallon Fuel Oil Tank
- · 8 Gallon Carb Compliant Engine Fuel Tank Belt Driven Pump
- Trigger Gun
- · Variable Pressure Wand
- · Downstream Chemical Injection
- · 50' Non Marking High Pressure Hose
- 'Hose Reel
- 40-Degree Nozzle
- Tandem Axle Trailer
- 4 & 6" Channel Iron & 3/16" Formed Steel Construction
- Extended A-Frame Coupler With 2 5/16" Ball Hitch
- Heavy Duty Jack With 2,000 LB. Wheel
- 15" Wheels And Tires
- · Electric Brakes
- Safety Brake Actuator
- Dual Safety Chains
- 12 Volt, D.O.T. Approved Light Package
- · 2 Each 225 Gallon Tanks
- 2 Each Heavy Duty Tool Boxes

Options:

- Hydromat, 14/ X 28'
- Pump W/Hose & Fittings, Wash Water Collection From Hydromat

Specifications

 Volume - GPM (LPM)
 5 (18.9)

 Pressure - PSI (BAR)
 3000 (207)

 Gasoline Engine
 19 HP

Dimensions, Inches (CM) 206" (523) L X 77" (196) W X 65" (165) H

Weight, Lbs (KG) 2700 (1225)











