



Decontamination System

Hydroblaster 5/3000GHO-WDS

UL1776, CSA and CE certifications

GENERAL SPECIFICATIONS AND USE

Hydroblaster 5/3000GHO-WDS is the most advanced and effective invasive species and watercraft decontamination system available. Features provide simplicity, efficiency, convenience, maximum safety, with ultimate performance for unparalleled real-world applications. In combination, Hydromat wastewater collection assures simple and portable environmental compliance.

Standard:

- Gasoline Engine
- 2400 Watt Generator
- Battery
- Full Locking Equipment Enclosure Schedule 80 Coil Warranty
- Control Panel
- 6 Gallon Fuel Oil Tank
- 8 Gallon Carb Compliant Engine Fuel Tank Belt Driven Pump
- Trigger Gun
- Variable Pressure Wand
- Downstream Chemical Injection
- 50' Non Marking High Pressure Hose
- 'Hose Reel
- 40-Degree Nozzle
- Tandem Axle Trailer
- 3/16" Formed Steel Construction
- Extended A-Frame Coupler With 2 5/16" Ball Hitch
- Heavy Duty Jack With 2,000 LB. Wheel
- 15" Wheels And Tires
- Trailer Mounted Spare Tire
- Electric Brakes
- Safety Brake Actuator
- Dual Safety Chains
- 12 Volt, D.O.T. Approved Light Package
- 2 Each 225 Gallon Tanks
- 2 Each Heavy Duty Tool Boxes



Options:

- Hydromat, 14/ X 28'
- Pump W/Hose & Fittings, Wash Water Collection From Hydromat

Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	3000 (207)
Gasoline Engine	19 HP
Dimensions, Inches (CM)	206" (523) L X 77" (196) W X 65" (165) H
Weight, Lbs (KG)	2700 (1225)

1. Specifications are effective 2024 2. Specifications are subject to change without notice



Certified Systems Available