

Hydroblaster Pressure Washer

10/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 10/3000EHOV high-pressure hot water systems provide flow of 10GPM with variable pressure up to 3000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- 208/230 Volt
- Hinged Access Equipment Enclosure
- Premium Efficiency Drive Motor
- Belt Driven Pump
- Schedule 80 Coil With Extended Warranty
- Automatic System Shutdown Timer
- Automatic Burner Ignition and Controls
- 13 Gallon Front Fill Fuel Oil Tank
- Trigger Gun System Discharge Control
- Dual Nozzle Variable Pressure Wand
- Discharge Soap/Chemical Injection



Optional Features

- Suitable For a Variety of Power Supplies Including 50Hz
- Lockable Power Disconnect Switch
- Hour Meter, Pressure and Temperature Gauges
- Trigger Actuated Start
- Remote Control Station In NEMA 4X Enclosures
- Stainless Trim; Pump Enclosure and Coil Housing
- Nozzle Options including Turbo Nozzle
- Plastic Float Tank
- Fresh/Recycle Water Supply w/Motorized Ball Valve
- Hose Reels
- HP Hose, Various Lengths

Specifications

Volume - GPM (LPM)	10 (37.8)
Pressure - PSI (BAR)	3000 (207)
BTU Minimum Supply	900000
Exhaust Diameter - Inch (mm)	10 (254)
Electric Motor - HP (KW)	20 (14.9)
Dimensions, Inches (cm)	50 (127) L x 34 (86.4) W x 58 (147) H
Weight, Lbs (kg)	1685 (764)
Frame	5EM964 (Md.)
Coil	24"
Burner	HD-501PC
SS Trim - Height	65 1/4"

Standard

Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	53	27

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)