Hydroblaster Pressure Washer

25/500 E - Water Cannon for Equipment Washing

Hydroblaster Model 25/500E Water Cannon provides industries most efficient and effective high-volume rinse or decontamination possible. Precision design balance of flow and pressure coupled with premier wand/nozzle combination optimize performance results. Operators have simple on-the-fly spray adjustment flexibility range from full fan to direct stream.

Applications can include heavy equipment decontamination, aircraft high volume rinse, or any application where engineered perfection of this Hydroblaster water cannon technology can benefit. Contact a Hydro Engineering, Inc. project manager for more information, application assistance or complete system design.

Model 25/500E equipment is certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt
Formed Steel Frame
500 Gallon (1,893 Liter) Cone Bottom Tank
Trigger Gun Wand and Nozzle Assembly
Hour Meter

Optional Features

No Tank With Flooded Suction Inlet
210 Gallon Cone Bottom Tank
Manual or Automatic Tank Sludge Drains
50 Hz Motor
Remote On/Off NEMA 4X Enclosure
Stainless Steel Cover and Panels
Select 50', 75', or 100' High Pressure Discharge Hose
Hose Reels, Manual or Spring Retract

Specifications

Volume - GPM (LPM)	25 (94.6)
Pressure - PSI (BAR)	500 (34.5)
Electric Motor - HP (KW)	10 (7.46)
Dimensions, Inches (cm)	112 (284.5) L X 43 (109) W X 96 (244) H
Weight, Lbs (kg)	1166 (529)

	Standard		
Volts (60Hz)	230V-3P	230V-1P	460V-3P
Amps (60Hz)	25	46	14

Pricing

For complete pricing details,
Submit a quote online below.

Get a Quote

Hydro Engineering Innovation | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

Subject to change without notice

Copyright Hydro Engineering Innovation 2025