

Hydroblaster Pressure Washer

4/2000 CLGV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 4/2000CLGV high-pressure hot water systems provide flow of 4GPM with variable pressure up to 2000PSI. All CLGV systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. Hydroblaster CLGV system design and quality manufacturing ensures continued performance, reliability and safety. All CLGV model Hydroblaster pressure washers are certified to UL-1776, CSA, and Conform to CE standards.

Standard Features

- 208/230 Volt
- Full Equipment Covers
- Belt Driven Pump
- Schedule 80 Coil Warranty
- Automatic Ignition
- Soap/Chemical Injection
- Exhaust Draft Diverter
- Variable Pressure Trigger Wand
- 15-Degree Nozzle
- Automatic Shutdown Timer



Optional Features

- 50-Hz Motor
- Power Vent
- Stainless Steel Trim
- Electrical Disconnect
- Float Tank
- [Remote Station Operation](#)
- Trigger Activated Start
- Pressure Gauge
- Hour Meter
- Select 50', 75' or 100' High Pressure Discharge Hose
- Hose Reel
- Nozzle Sets
- [Turbo Nozzle](#)

Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	2000 (138)
BTU Minimum Supply	325000
Exhaust Diameter - Inch (mm)	8 (203.2)
Electric Motor - HP (KW)	5 (3.7)
Dimensions, Inches (cm)	45 (114.3) L X 26 (66) W X 51 (129.5) H
Weight, Lbs (kg)	605 (274)

Standard

Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	23	14	7

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)