Hydroblaster Pressure Washer

4/2000 E - Electric Motor, Cold Water Pressure Washer

Hydroblaster 4/2000E high-pressure cold water systems provide flow of 4GPM with variable pressure up to 2000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All E model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt
Fully Hinged Equipment Enclosure
Belt Driven Pump
Variable Pressure Wand
Trigger Gun
15-Degree Nozzle
Hour Meter

Optional Features

50-Hz Motor
Stainless Steel Covers
Electrical Disconnect
Float Tank
Automatic Shut Down Timer
Remote Station Operation
Trigger Activated Start
Pressure Gauge
Non Marking, Discharge Hose
Hose Reel
Nozzle Sets
Turbo Nozzle

Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	2000 (138)
Electric Motor - HP (KW)	5 (3.73)
Dimensions, Inches (cm)	32 (81.3) L X 25 (63.5) W X 39 (99) H
Weight, Lbs (kg)	420 (191)

	Standard		
Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	25	14	7

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote

Hydro Engineering Innovation | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

Subject to change without notice

Copyright Hydro Engineering Innovation 2025