

# Hydroblaster Pressure Washer

## 4/2000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 4/2000EHOV high-pressure hot water systems provide flow of 4GPM with variable pressure up to 2000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

### Standard Features

- 208/230 Volt
- Hinged Access Equipment Enclosure
- Premium Efficiency Drive Motor
- Belt Driven Pump
- Schedule 80 Coil With Extended Warranty
- Automatic System Shutdown Timer
- Automatic Burner Ignition and Controls
- 6 Gallon Front Fill Fuel Oil Tank
- Trigger Gun System Discharge Control
- Dual Nozzle Variable Pressure Wand
- Discharge Soap/Chemical Injection



### Optional Features

- Suitable For a Variety of Power Supplies Including 50Hz
- Lockable Power Disconnect Switch
- Hour Meter, Pressure and Temperature Gauges
- Trigger Actuated Start
- Remote Control Station In NEMA 4X Enclosures
- Stainless Trim; Pump Enclosure and Coil Housing
- Nozzle Options including Turbo Nozzle
- Plastic Float Tank
- Fresh/Recycle Water Supply w/Motorized Ball Valve
- Hose Reels
- HP Hose, Various Lengths

### Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	2000 (138)
BTU Minimum Supply	360000
Exhaust Diameter - Inch (mm)	8 (203.2)
Electric Motor - HP (KW)	5 (3.73)
Dimensions, Inches (cm)	42.25 (115) L X 31.75 (80.6) W X 58 (149) H
Weight, Lbs (kg)	695 (315)
Frame	5BK169 (Sm.)
Coil	18"
Burner	HD-401PC
SS Trim - Height	53 7/8"

#### Standard

<b>Volts (60Hz)</b>	230V-1P	230V-3P	460V-3P
<b>Amps (60Hz)</b>	23	14	7

### Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)