Hydroblaster Pressure Washer

4/2000 ES - Electric Motor, Cold Water Pressure Washer

Hydroblaster 4/2000ES high-pressure cold water systems provide flow of 4GPM with variable pressure up to 2000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All ES model Hydroblaster pressure washers are certified to UL-1776,CSA,and conform to CE standards.

Standard Features

208/230 Volt
Full Equipment Enclosure
System Shut Down Timer
Variable Pressure Wand
Trigger Gun
15-Degree Nozzle
Stackable Design, up to four (4) high
Hour Meter

Optional Features

Electrical Disconnect
Remote Control Start/Stop Stations
Trigger Operated Start/Stop
50 Hz Electrical
Pressure Gauge
Select 30',50',75' or 100' High Pressure Discharge Hose
Hose Reel
Nozzle Sets
Turbo Nozzle
Discharge Soap Injection
Breaker (Float) Tank
Compact floor mount stand with forklift slots

Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	2000 (138)
Electric Motor - HP (KW)	5 (3.7)
Dimensions, Inches (cm)	38 (96.5) L X 19 (48.3) W X 21 (53.3) H
Weight, Lbs (kg)	370 (168)

	Standard		
Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	25	14	7

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote

Hydro Engineering Innovation | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

Subject to change without notice

Copyright Hydro Engineering Innovation 2025