

Hydroblaster Pressure Washer

4/3000 EHG V - Electric Motor, Hot Water Pressure Washer

Hydroblaster 4/3000EHGV high-pressure hot water systems provide flow of 4GPM with variable pressure up to 3000PSI. All EHG V systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHG V model Hydroblaster pressure washers are certified to UL-1776, CSA. and conform to CE standards.

Standard Features

- 208/230 Volt
- Hinged Access Equipment Enclosure
- Premium Efficiency Drive Motor
- Belt Driven Pump
- Schedule 80 Coil With Extended Warranty
- Draft Diverter
- Automatic System Shut Down Timer
- Automatic Burner Ignition and Controls
- Trigger Gun System Discharge Control
- Discharge Soap/Chemical Injection
- Dual Nozzle Variable Pressure Wand



Optional Features

- Suitable For a Variety of Power Supplies Including 50Hz
- Power Vent Burner Exhaust
- Lockable Power Disconnect Switch
- Hour Meter, Pressure and Temperature Gauges
- Trigger Actuated Start
- Remote Control Station In NEMA 4X Enclosures
- Stainless Trim: Pump Enclosure and Coil Housing
- Nozzle Options including Turbo Nozzle
- Plastic Float Tank
- Fresh/Recycle Water Supply w/Motorized Ball Valve
- Hose Reels
- HP Hose, Various Lengths

Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	3000 (207)
BTU Minimum Supply	325000
Exhaust Diameter - Inch (mm)	10 (254)
Electric Motor - HP (KW)	7.5 (5.59)
Dimensions, Inches (cm)	45.25 (115) L X 31.75 (80.6) W X 55 (139.7) H
Weight, Lbs (kg)	718 (326)
Frame	5BK169 (Sm.)
Coil	20"
Burner	X11

Standard

Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	33	22	11

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)