

Hydroblaster Pressure Washer

5/3000 EE - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/3000EE high-pressure hot water systems provide flow of 5 GPM with variable pressure up to 3000 PSI. All EE systems are electrically heated systems designed for use in environmentally sensitive areas and do not have an open flame. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EE model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards and heating modules are CSA approved.

Standard Features

- 208/230 Volt
- Full Equipment Covers
- Belt Driven Pump
- Low Heater Solution Shut Down
- Variable Pressure Trigger Wand
- 15-Degree Nozzle

Optional Features

- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Automatic Shut Down Timer
- [Remote Station Operation](#)
- Trigger Activated Start
- Pressure Gauge
- Hour Meter
- [High Pressure Soap/Chemical Injection](#)
- Select 50', 75', or 100' High Pressure Discharge Hose
- Hose Reel
- Nozzle Sets
- [Turbo Nozzle](#)



Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	3000 (207)
Electric Heating System - KW	48
Electric Motor - HP (KW)	10 (7.46)
Dimensions, Inches (cm)	32 (81.3) L X 24 (60.9) W X 50 (126) H
Weight, Lbs (kg)	565 (256)

	Standard	
Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	154	71

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)