Hydroblaster Pressure Washer

5/3000 EHGV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/3000EHGV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 3000PSI. All EHGV systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHGV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt
Hinged Access Equipment Enclosure
Premium Efficiency Drive Motor
Belt Driven Pump
Schedule 80 Coil With Extended Warranty
Draft Diverter
Automatic System Shut Down Timer
Automatic Burner Ignition and Controls
Trigger Gun System Discharge Control
Discharge Soap/Chemical Injection
Dual Nozzle Variable Pressure Wand
Hour Meter

Optional Features

Suitable For a Variety of Power Supplies Including 50Hz
Power Vent Burner Exhaust
Lockable Power Disconnect Switch
Pressure and Temperature Gauges
Trigger Actuated Start
Remote Control Station In NEMA 4X Enclosures
Stainless Trim: Pump Enclosure and Coil Housing
Nozzle Options including Turbo Nozzle
Plastic Float Tank
Fresh/Recycle Water Supply w/Motorized Ball Valve
Hose Reels
HP Hose, Various Lengths

Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	3000 (207)
BTU Minimum Supply	400000
Exhaust Diameter - Inch (mm)	10 (254)
Electric Motor - HP (KW)	10 (7.46)
Dimensions, Inches (cm)	45.25 (115) L X 31.75 (80.6) W X 55 (139.7) H
Weight, Lbs (kg)	710 (322)
Frame	5BK169 (Sm.)
Coil	20"
Burner	X44

	Standard	
Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	25	13

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote

Hydro Engineering Innovation | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

Subject to change without notice

Copyright Hydro Engineering Innovation 2026