

Hydroblaster Pressure Washer

5/5000 EHGV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/5000EHGV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 5000PSI. All EHGV systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHGV model Hydroblaster pressure washers are certified to UL-1776, CSA. and conform to CE standards.

Standard Features

208/230 Volt

Hinged Access Equipment Enclosure
Premium Efficiency Drive Motor
Belt Driven Pump
Schedule 80 Coil With Extended Warranty
Draft Diverter
Automatic System Shut Down Timer
Automatic Burner Ignition and Controls
Trigger Gun System Discharge Control
Discharge Soap/Chemical Injection



Optional Features

Suitable For a Variety of Power Supplies Including 50Hz Power Vent Burner Exhaust

Lockable Power Disconnect Switch

Dual Nozzle Variable Pressure Wand

Hour Meter, Pressure and Temperature Gauges

Trigger Actuated Start

Remote Control Station In NEMA 4X Enclosures

Stainless Trim: Pump Enclosure and Coil Housing

Nozzle Options including Turbo Nozzle

Precision (Peristaltic Pump) Inlet Soap

Soap Injection Flow Meter

Plastic Float Tank

Fresh/Recycle Water Supply w/Motorized Ball Valve

Hose Reels

HP Hose, Various Lengths

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote







Hydroblaster Pressure Washer

5/5000 EHGV - Electric Motor, Hot Water Pressure Washer

Specifications

Volume - GPM (LPM) 5 (18.9)
Pressure - PSI (BAR) 5000 (345)
BTU Minimum Supply 400000
Exhaust Diameter - Inch (mm) 10 (254)
Electric Motor - HP (KW) 20 (14.9)

Dimensions, Inches (cm) 45.25 (115) L X 31.75 (80.6) W X 55 (139.7) H

Weight, Lbs (kg) 785 (356) Frame 5BK169 (Sm.)

Coil 20" Burner X44

Standard

Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	53	27

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



