

Hydroblaster Pressure Washer

5/5000 G - Engine Driven, Cold Water Pressure Washer

Hydroblaster 5/5000G engine-driven, high-pressure cold water systems provide flow of 5-gpm with variable pressure up to 5000-psi. Hydroblaster G system design and quality manufacturing ensures continued performance, reliability and safety. All G model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

Formed Steel Base W/ Forklift Slots
Full Steel Cage Protection
1.8 Gallon Fuel Tank
Direct Driven Pump
Trigger Gun
Variable Pressure Wand
Downstream Chemical Injection
50' (15M) High Pressure Discharge Hose
15-Degree Nozzle
Portability Kit - Casters



Battery - Lead Acid
Battery - Spiral Cell
Pressure Gauge
Hour Meter
Nozzle Sets
Turbo Nozzle
Hose Reel
Discharge Hose Lengths



Specifications

Volume - GPM (LPM) 5 (18.9) Pressure - PSI (BAR) 5000 (345)

Gasoline Engine - HP 25

Dimensions, Inches (mm) 38" (965) L X 18" (457) W X 27" (686) H

Weight, Lbs (kg) 465 (211)

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



